



# HK2288

## Home Cinema Projector

Bright ultraHD projector  
for the home cinema  
enthusiast



### Features

- Ultra HD 4K (8.3 million pixels) resolution for outstanding details and stunning visuals
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels, and vibrant, colorful images
- Up to 2,000 ANSI lumens for an amazing brightness
- Extremely high 1,000,000:1 contrast ratio for spectacular blacks and outstanding colors
- Advanced video processor for streaming stability and 12-bit programmable RGB color adjustments
- High Dynamic Range (HDR10) for enriched brightness and impeccable vibrancy for precise natural color reproduction
- REC 709 for an incredible cinematic experience
- Six-segment RGB color wheel delivers outstanding reds, greens, and blues
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Advanced HDMI 2.0 (x3) connectors for high-quality digital video signals and quick data transfer rates
- Long lasting energy efficient lamps that last up to 4,000 hours (Dynamic Economy Mode)
- Wide 1.5x zoom range and vertical lens shift for greater installation convenience and flexibility
- Full-functioning remote with intuitive key pad for easy control
- Dual infrared sensors for handy remote control from either in front or behind the projector
- AVAILABLE IN WHITE ONLY





# HK2288

## SPECIFICATION



<b>Display Type/Chip Size</b>	DLP® 0.66" TRP by Texas Instruments
<b>Brightness</b>	2,000 ANSI Lumens
<b>Native Resolution</b>	UHD (3,840 x 2,160)
<b>Maximum Resolution</b>	UHD (3,840 x 2,160)
<b>Contrast Ratio (Typical)</b>	1,000,000:1
<b>Lamp Life/Type</b>	2,500/3,500/4,000 Hours (Normal/Eco./Dynamic Eco. Mode), 310W
<b>Throw Ratio</b>	1.39 – 2.09:1
<b>Image Size (Diagonal)</b>	26" – 324.9" (0.6m – 8.25m)
<b>Projection Distance</b>	3.9' – 32.8' (1.2m – 10m)
<b>Projection Lens</b>	F= 2.42 – 2.97 f=20.70 – 31.05
<b>Zoom Ratio</b>	1.5x
<b>Native Aspect Ratio</b>	16:9
<b>Vertical Scan Rate</b>	24 – 30Hz , 47 – 120Hz
<b>Horizontal Frequency</b>	31 – 131kHz
<b>Lens Shift Range</b>	Vertical: 5% – 10%
<b>Speaker</b>	10W (Mono)
<b>I/O Connection Ports</b>	HDMI v2.0 (x3), Audio-Out (Mini-Jack), USB Type A Power (5V/1.5A), Mini-USB (Service), RS-232
<b>Dimensions (W x D x H)</b>	16.9" x 14.2" x 5.7" (430 x 360 x 145mm)
<b>Weight (W/STDLens)</b>	19.81lbs (9kg)
<b>Noise Level</b>	35dB/TBDdB (Normal/Eco. Mode)
<b>Power Consumption</b>	450W (Normal Mode), 380W (Eco. Mode), <0.5W (Standby Mode)
<b>UPC:</b>	813097023292

TEL: +1-855-885-2378 | [WWW.VIVITEKUSA.COM](http://WWW.VIVITEKUSA.COM) | 46101 FREMONT BLVD., FREMONT, CA 94538 USA

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.