



Professional-Grade XGA Multimedia Projector for the Large Venue Marketplace

The Vivitek D5000 XGA digital projector utilizes the latest advancements in video processing technologies to create remarkable image quality. A professional-grade projector with the large venue marketplace in mind, the D5000 delivers amazing video performance. With manual lens shift functions and multiple connectivity alternatives, the Vivitek D5000 is the most comprehensive projector to create a superior picture in a large venue environment.

Features

- 5200 lumens and 2500:1 contrast ratio
- 3D-ready via DLP® Link™
- DLP and BrilliantColor™ technologies by Texas Instruments
- Three (3) interchangeable lens options and manual lens shift (vertical/horizontal) for easy setup
- Connectivity options include: HDMI v1.3, DVI-D, VGA-In, BNC, Component, S-Video, Composite
- RS-232c/RJ45 for integration and system administration
- 12V trigger for simple screen/projector automation



Specifications	
Brightness	5200 Lumens (Typical)
Native Resolution	XGA (1024 x 768)
Max. Resolution	SXGA+ (1400 x 1050)
Contrast Ratio	2500:1 (Full On/Full Off)
Lamp Life and Type	≈2000/1500 Hours (Standard/Boost Mode), 330W UHP
Lamp Part #	5811116765-S
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Aspect Ratio	4:3 Native, 16:9 Compatible
Keystone Correction	±15° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	50 to 85 Hz
Speakers Output	6 Watts (3W Mono x2)
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, DVI-D, Component Video, BNC, VGA-In (x2), Composite Video, VGA-Out, S-Video, RCA Stereo-In (x2), Mini-jack Audio-In (x3), Mini-jack Audio-Out, RJ45, RS-232c, 12V Trigger, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	19 lbs (8.6 kg)
Dimensions (W x H x D)	16.97" x 6.36" x 13.55" (431 x 161 x 344 mm)
Noise Level	37dB/33dB (Boost/Standard Mode)
Power	Supply: AC 100-240V, 50 / 60Hz Consumption: 335W (Standard Mode), 390W (Boost Mode), <1W(Standby)
Operating Temperature	41 to 104°F (5 to 40°C), 80% Max Humidity
Warranty	3-Year Limited Parts/Labor, 1-Year Lamp
Standard Accessories	AC Power Cord, VGA Cable, Standard Lens, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
UPC	8 14964 33525 8

Lens Part No.	VL901G (Standard Zoom Lens)	VL903G (Short Wide Fixed Lens)	VL905G (Long Zoom Lens)
Throw Ratio (±3%)	1.6 to 2.0:1 (Distance/Width)	0.8:1 (Distance/Width)	2.0 to 3.0:1 (Distance/Width)
Image Size (Diagonal)	37" to 300" (0.9 to 7.6 m)	37" to 200" (0.9 to 5.1 m)	37" to 450" (0.9 to 11.4 m)
Projection Distance	3.9' to 40.0' (1.2 to 12.2 m)	2.0' to 10.7' (0.6 to 3.3 m)	4.9' to 90.0' (1.5 to 27.4 m)
Zoom Ratio	1.25:1 Manual Zoom/Focus	Fixed Lens, Manual Focus	1.5:1 Manual Zoom/Focus
Lens Shift Range	Vertical: ±100%, Horizontal: ±20%	Vertical: ±100%, Horizontal: ±20%	Vertical: ±100%, Horizontal: ±20%