



## Extreme Short-Throw Advantages with Crossover Possibilities

The Vivitek D795WT WXGA crossover projector can create a 93" image from about 1.3' away. This extreme short-throw projector features 3000 lumens of brightness, a 2500:1 contrast ratio, DLP® and BrilliantColor™ technologies for impressive color reproduction and amazing picture performance. With its assortment of connectivity options and a built-in speaker, the D795WT is the ultimate solution for the latest multimedia and widescreen needs.

### Features

- 3000 lumens of brightness with a 2500:1 contrast ratio
- 3D-ready via DLP® Link™
- DLP and BrilliantColor technologies by Texas Instruments
- Connectivity options include: HDMI v1.3, two (2) VGA-in, composite video, S-video
- VividWheel III for improved color reproduction and automatic gain control
- Top-loading, cover for quick and easy lamp replacement

Specifications	
Brightness	3000 Lumens (Typical)
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2500:1 (Full On/Off)
Lamp Life and Type	≈4000/6000 Hours ( Boost/Standard Mode), 220W
Lamp Part #	5811116635-S
Display Type	Single DMD DLP® Technology by Texas Instruments
Throw Ratio (±3%)	0.19:1 (Distance/Width)
Image Size (Diagonal)	86.7" to 97" (2.2 to 2.4 m)
Projection Distance	0.88" ±0.4" to 2.45" ±0.4" (22.4 ±10 mm to 62.3 ±10 mm)
Projection Lens	F=2.4
Zoom Ratio	Fixed Lens, Manual Focus
Aspect Ratio	16:10 Native, 16:9 & 4:3 Compatible
Offset	13.5" to 14.5" (342 to 368.3 mm)
Keystone Correction	±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	10W Mono
Remote Control	Fully Featured IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i), EDTV (480p), HDTV (576i/p, 720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.3, VGA-In (x2), VGA-Out, Composite Video, S-Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, RJ45, RS-232c, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	19.84 lbs (9.0 kg)
Dimensions (W x H x D)	13.94" x 8.62" x 16.16" (354 x 219 x 410.5 mm)
Noise Level	27dB/29dB (Standard/ Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290W (Boost Mode), 240W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Parts/Labor, 90-Day Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, User Manual (CD), Warranty Card
UPC	8 14964 33524 1

