



## Heighten Your Viewing Experience

The Vivitek D803W-3D is a high-performance digital projector that offers outstanding digital images with full color saturation. D803W-3D features native WXGA resolution, multiple connectivity options and 3600 lumens of brightness. With a 3D function and the capability to convert 2D content into 3D from pretty much any video source without an external box. The Vivitek D803W-3D digital projector takes standard and 3D to another level.

## Features

- Native WXGA resolution and displays up to UXGA
- 3600 lumens of brightness and a 15000:1 contrast ratio
- 2D to 3D conversion via HDMI
- Connect directly to any standard or 3D Blu-Ray™ player for 3D viewing
- View latest 3D content being broadcasted via cable or satellite
- DLP/BrilliantColor™ technologies by Texas Instruments
- Built-in 10W speaker
- High-efficiency lamps that last up to 4000 hours (in standard mode)
- Connectivity options include: Two (2) HDMI v1.3, VGA-In, S-Video, Composite Video, Audio-In
- RS-232c for projector control and management

Specifications	
Brightness	3600 Lumens (Typical)
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	15,000:1 (Full On/Off)
Lamp Life and Type	4000/3000 Hours (Standard/Boost), 240W UHP
Lamp Part #	5811117901-SVV
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio (±3%)	1.54 to 1.7:1 (Distance/Width)
Image Size (Diagonal)	25" to 300" (0.6 to 7.6 m)
Projection Distance	3.94' to 32.8' (1.2 to 10m)
Projection Lens	F=2.50-2.72, f=17.81-21.35mm
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	16:10 Native, 4:3, 16:9 Compatible
Offset	123%
Keystone Correction	±40° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 120Hz
Speaker	10W Mono
Remote Control	20-Key IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
3D Video Compatibility	720p 50/60 Frame Packing, 1080i 50/60 Side-by-Side, 1080p24 Frame Packing
2D Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3 (x2), Component-In, VGA-In, Composite Video, S-Video, RCA Stereo-In, Mini-Jack Audio-In, Mini-Jack Audio-Out, RS-232c, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	8.0 lbs (3.63 kg)
Dimensions (W x H x D)	11.2" x 5.12" x 10.3" (285 x 130 x 261 mm)
Noise Level	32dB/34dB (Standard/Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Standard), 260W (Boost), <0.5W (Standby)
Operating Temperature	41 to 95°F (5 to 35°C), 80% Max Humidity
Warranty	3-Year Limited Parts/Labor, 1-Year Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, Warranty Card, User's Manual (CD)
UPC	814964 336910

