



Features

- Native XGA (1024 x 768) resolution with display up to WUXGA (1920 x 1200)
- High brightness of 6000 ANSI lumens and high 10,000:1 Contrast ratio ensuring a crisp and sharp image
- 5-segment color wheel for exceptional color reproduction
- 3D-ready via DLP® Link™ and BluRay 3D movie playback
- Connectivity options include: HDMI V1.4 (x2), Display Port, VGA-in (x2), VGA out, Composite video, S-Video
- DLP® dark chip 3 and BrilliantColor™ technologies for sharp and detailed image quality
- 3D-ready via DLP® Link™ and BluRay 3D movie playback
- New efficient lamp offering up to 4,000 hours of life
- Connectivity options include: HDMI V1.4 (x2), Display Port, VGA-in (x2), VGA out, Composite video, S-Video
- VGA-output for display on a secondary monitor
- RJ45/RS-232c for integration and system administration
- Crestron® RoomView™ certified
- 12V trigger for simple screen/projector automation
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments



Specifications				
Brightness (Typical)	6,000 ANSI Lumens			
Native Resolution	XGA (1024 x 768)			
Max. Resolution	WUXGA (1920 x 1200)			
Contrast Ratio	10,000:1 (Full On/Off)			
Lamp Life and Type	2500/3500/4000 Hours (Normal/Eco/Dynamic Eco), 310W			
Lamp Part #	5811118436-SVV			
Display Type	Single 0.7" DLP® Technology by Texas Instruments			
Throw Ratio (±3%)	1.8 to 2.1:1 (Distance/Width)			
Image Size (Diagonal)	23.4" to 300" (0.6 to 7.6 m)			
Projection Distance	4.92' to 32.8' (1.5 to 10 m)			
Projection Lens	F=2.6-2.81, f=26.01- 29.84 mm			
Zoom Ratio	1.15:1 Manual Zoom/Focus			
Aspect Ratio	4:3 Native, 16:9 Compatible			
Offset	124%			
Keystone Correction	± 40° Vertical (± 40 steps)			
Color Spectrum	16.7 Million			
Horizontal Scan Rate	15, 31 ~ 91.4KHz			
Vertical Scan Rate	24 ~ 30Hz, 47 ~ 120Hz			
3D Functionality	Full 3D (Via DLP® Link™, BluRay 3D)			
Speaker	5W Mono			
Remote Control	Fully Featured IR Remote with Laser Pointer			
Projection Method	Table Top or Ceiling Mount (Front or Rear)			
Uniformity	85%			
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible			
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM			
I/O Connection Ports	HDMI v1.4 (x2)	RJ45		
	Display Port	RS-232c		
	VGA	VGA-In (x2)	Audio-In	RCA L/R
		VGA-Out		Mini-Jack
	S-Video		Audio-Out Mini-Jack	
	Video		12-V Trigger	
	3D Sync		USB (Service Only)	
Security	Kensington® Lock Port, Security Bar			
Weight	8.3lbs (3.76kg)			
Dimensions (W x H x D)	13.1" x 4.5" x 10" (333 x 115 x 255 mm)			
Noise Level	35dB/40dB (Eco/Normal)			
Power	Supply: AC 100-240V, 50/60Hz Consumption: 300W/370W (Eco/Normal) <0.5W (Standby Mode)			
Operating Temperature	41 to 104°F (5 to 40°C)			
Warranty	3-Year Limited Parts/Labor, 1-Year Lamp			
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User Manual (CD), Warranty Card			
UPC	813097022462			

