



Full HD 3D ready projector

The Vivitek DH558 is a Full HD digital projector that features 3000 lumens, a 15,000:1 contrast ratio and DLP®/BrilliantColor™ technologies to deliver crisp, and vibrant images. With 3D-ready via DLP Link™, the DH558 can display 3D sources, such as, a 3D Blu-Ray™ player or broadcast 3D. Built with true HD 1080p widescreen resolution, enhanced color performance and HDMI v1.4, the Vivitek DH558 is the right choice for the latest video content.

Features

- Native 1080p (1920x1080) resolution
- 3000 lumens of brightness and a 15,000:1 contrast ratio
- High-efficiency lamps that last up to 10,000 hours (in Dynamic Eco mode)
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- DLP/BrilliantColor™ technology by Texas Instruments
- 3D-Ready via DLP® Link™, Full 3D From Blu-Ray™ or broadcasted via cable or satellite
- Audio ready with built-in 2 watts audio speaker
- Audio-in and Audio-out ports
- RS-232c for integration and system administration compatible with Crestron, AMX, and Extron
- Top-loading cover for quick and easy lamp replacement
- Keypad lock feature to avoid accidental change to the setting
- Compatible with long VGA cables for a maximum length up to 20 meters

Specifications		
Brightness	3000 Lumens	
Native Resolution	1080p (1920 x 1080)	
Contrast Ratio	15,000:1 (Full On/Off)	
Lamp Life and Type	5,000/6,000/10,000 (Normal/Eco/Dynamic Eco Mode), 190W	
Lamp Part #	5811118154-SVV	
Display Type	Single 0.65" DC3 DMD DLP® Technology by Texas Instruments	
Throw Ratio (±3%)	1.22 to 1.46:1 (Distance/Width)	
Image Size (Diagonal)	30.9" to 370.3" (0.78 to 9.40m)	
Projection Distance	3.287' to 32.8' (1 to 10m)	
Projection Lens	F= 2.5 - 2.72, f= 17.81 - 21.35mm	
Zoom Ratio	1.2:1 Manual Zoom/Focus	
Aspect Ratio	16:9 Native , 4:3 Compatible	
Offset	115%	
Keystone Correction	±40° Vertical	
Color Spectrum	1.07 Billion	
Horizontal Scan Rate	2D: 15, 30 to 91.4KHz/ 3D: 101.6 KHz	
Vertical Scan Rate	24~30, 47~120 Hz	
Speaker	2 Watt Mono	
Remote Control	Name Card-Type IR Remote	
Projection Method	Table Top or Ceiling Mount (Front or Rear)	
Uniformity	95%	
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resize; VESA Standards; PC and Macintosh Compatible	
3D Ready	Yes (DLP® Link™, Full 3D from Blu-Ray or broadcasted via cable or satellite)	
2D Video Compatibility	SDTV(480i, 576i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM	
I/O Connection Ports	HDMI v1.4 / MHL	Audio-In
	VGA-In	Audio-Out
	VGA-Out	USB Power (5V / 1.5A)
	RS-232c	Mini-USB (Service Only)
Security	Kensington® Lock Port. Keypad Lock	
Weight	5.1lbs (2.3 kg)	
Dimensions (W x H x D)	10.8" x 3.94" x 8.35" (275 x 212 x 100)	
Noise Level	34dB/31dB (Standard/Economy Mode)	
Power	Supply: AC 100-240V, 50/60Hz Consumption: 200W (Economy Mode), 240W (Standard Mode), 0.5W (Standby Mode)	
Operating Temperature	41 to 104°F (5 to 40°C)	
Warranty	3-Year Limited Parts/Labor, 1-Year on Lamp	
Standard Accessories	AC Power Cord, VGA Cable, HDMI Cable, Remote Control with Battery User's Manual (CD) Warranty Card	
UPC	813097021083	

