

LARGE VENUE
3D PROJECTOR | **DU5671**

High brightness professional-grad WUXGA projector with full connectivity and HDBaseT™



Features

- DLP and BrilliantColor™ technologies by Texas Instruments
- Up to 6,200 ANSI lumens with a 2,000:1 contrast ratio
- Native WUXGA resolution with a maximum WUXGA resolution
- Manual zoom and focus for easy adjustment and positioning flexibility
- Centered lens for easy installation
- Horizontal and vertical lens shift (manual) for greater installation convenience and flexibility
- Distorted and trapezoid image issues are easily corrected with H/V keystone, and 4-corner adjustment
- Full suite of display connectivity inputs and outputs including: HDMI v1.4b, DVI-D, Composite Video, S-Video, Component (5 BNC) (RGBHV), VGA-In, VGA-Out
- HDBaseT™ interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- 3D compatibility with DLP® Link™ and HDMI 1.4 Blu-Ray technology support
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- RS-232c/RJ45 ready for integration and system automation
- Crestron® RoomView™ integration for network monitoring and management
- Seven (7) interchangeable lens options with quick touch lens release design for easy lens installation/removal
- Anti-theft security features include: Kensington® security slot, and security bar

Photos



Specifications		
Display Type	Single Chip 0.67" DLP Technology by TI	
Brightness	6,200 ANSI Lumens	
Native Resolution	WUXGA (1920 x 1200), 16:10 format	
Contrast Ratio	2,000:1	
Lamp Life/Type	1,500/2,000 hours (Normal/Eco Mode), 430W/230W	
Throw Ratio*	1.54 - 1.93:1	
Image Size (Diagonal)*	35.1" – 205.3"	
Projection Distance*	4.9ft - 22.96ft (1.5m – 7m)	
Zoom Ratio*	1.25x	
Aspect Ratio	16:10	
Keystone Correction	Vertical ±30°, Horizontal ±30°	
Horizontal Frequency	15, 31 - 91.4Hz	
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz	
3D	Yes (DLP® Link™, HDMI 1.4 (Blu-Ray 3D))	
Speaker	3W (x1)	
Lens Shift Range*	Vertical: -20% - +60%, Horizontal: -5% - +5%	
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac	
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)	
Keystone Correction	Vertical ±30°, Horizontal ±30°	
I/O Connection Ports	HDMI v.1.4 (x2)	VGA-Out
	HDBaseT™	Audio-Out (Mini-Jack)
	DVI-D	3D-Sync-Out
	5 BNC (RGBHV/Component)	5V/1.5A Out (USB Type A)
	VGA-In (x2)	12V Trigger
	S-Video	RJ45
	Composite Video	RS-232
	Audio-IN	RCA (L/R) / Mini-Jack (x2)
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock	
Dimensions (WxDxH)	17"x 13.5" x 7.1" (431 x 344 x 180mm)	
Weight	19.4lbs (8.8Kg)	
Available Colors	White	
Noise Level	43dB/38dB (Normal/Eco. Mode)	
Power Supply	AC 100-240V, 50/60Hz	
Power Consumption	540W (Normal Mode), 460W (Eco. Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)	
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit	
Optional Accessories	Interchangeable Lens Options (x7)	
Lamp Part number	5811122169-SVV, (Lamp UPC #813097023773)	
UPC Code (Projector)	813097023384	

*Note: Standard Lens

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

