



Flagship Large Venue Projector

DU9057Z

Super-bright with Dual Laser projector delivering 27,000 lumens.
Rich connectivity, Optimal Brilliant Color performance and
30,000 hours of operational time

Features

- Solid state laser phosphor light source for reliable projection and performance
- Environmentally friendly lamp-less design that is mercury-free and energy efficient
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- 27,000 lumens with a dynamic 20,000:1 contrast ratio for an amazing image quality
- Embedded smart sensor detects the brightness levels and automatically adjusts the output levels to ensure a constant bright image
- With red Laser light source produces rich colors for an incredible cinematic like movie experience
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Almost maintenance-free with up to 30,000 hours of operating time
- Native WUXGA resolution with a maximum 4K UHD resolution
- Built-in hardware edge blending and warping functionality
- Powered zoom, focus and lens shift (horizontal/vertical) for easy adjustment and positioning flexibility
- Lens Positioning Memory (LPS) for quick recall of user defined lens positions (focus, zoom and lens shift)
- Full suite of display connectivity inputs including: HDMI v2.0, DVI-D, 12G-SDI-In/Out, HDBaseT™
- HDBaseT™ interface with support for distribution of digital HD video content over standard CAT5e/6 LAN cable
- Frame sequential and dual channel 3D support
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- 360° operation and projection design for set up in all angles
- Instantaneous power-on & off, so no need for system pre-heating and post-cooling
- Crestron® RoomView™ integration for network monitoring and management
- Eight (7) interchangeable lens options with quick touch lens release design for easy lens removal and reinstallation from TR0.38 & 0.9 to 10.3
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Optimized system layout with high efficiency air cooling system
- Heavy duty steel chassis for extra strength and integrity
- 24/7 continuous operation with no downtime
- Network ready for integration and system administration via RJ45
- LCM information indicator, read information directly
- Support Art-Net Stage console control system
- Provide Rental mode for rental marketing
- New Color uniformity correction
- Warp and Blending auto calibration with mobile phone

Photos



Specifications

Display Type	Single Chip 0.96" DLP Technology by TI	
Brightness*	27,000 Lumens	
Native Resolution	WUXGA (1920 x 1200)	
Maximum Resolution	4K UHD (3840x2160) @60Hz	
Contrast Ratio	1,500:1 (Native) / 20,000:1 (Dynamic) / 3,000,000:1 (Full On/Off)	
Laser Life/Type	Up to 30,000 hours / Dual Laser Technology	
Throw Ratio**	1.5 - 2.0:1	
Image Size (Diagonal) **	40" - 500"	
Projection Distance**	1.24 - 21.8m (4.06ft to 71.5ft)	
Projection Lens**	F = 2.17 – 2.65	
Zoom Ratio**	1.33:1	
Aspect Ratio	16:10	
Offset	Motorized Lens Shift	
Lens Shift Range**	Vertical: ±50%, Horizontal: ±15%	
Keystone Correction	Horizontal ±45°, Vertical ±40° (Adjustable Range of Single Direction)	
Horizontal Frequency	15.31 ~ 135 kHz	
Vertical Scan Rate	24~30Hz ;47~120Hz	
Edge Blending	Yes (Built-In)	
Warping	Yes (Built-In)	
3D Functionality	Yes (DLP® Link™, HDMI v2.0 Blu-ray, (side by side, frame packing, top and bottom, frame sequential) VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, 1080P, WUXGA, 4k UHD@60Hz, Mac	
Computer Compatibility		
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p, 4K UHD)	
I/O Connection Ports	HDMI v2.0 (x2) (HDCP v2.2 Compliant), DVI-D x1, 12G SDI-In/Out, 3D Sync In/Out, 3D IR Sync Out x1, RS232-in x1, 12v Trigger, Wired Remote in/out, USB 5V2A, HDBaseT™ x1 (Video only), LAN (RJ45) x1	
Projection Method	Table Top, Ceiling Mount, Portrait (Front or Rear)	
Dimensions (WxDxH)	676.6 x 598.8 x 270mm (29.7" x 23.6" x 10.6")	
Weight	45.4kg (100 lbs)	
Available Colors	Black	
Noise Level	48dB / 46dB (Normal / Eco Mode)	
Power Supply	AC 100-240V, 50/60Hz	
Power Consumption	Normal \ Eco	1500W@220Vac \ 1150W@220Vac
	Network Standby	Less than 6W
	Eco Standby	Less than 1W
Environmental Conditions	Operating	At temperature 0 to 40°C, relative humidity 10% to 85%, non-condensation
	Storage	At temperature -10 to 60°C, relative humidity 5% to 95%, non-condensation
Standard Accessories	AC Power Cord, Remote Control w/Batteries, HDMI Cable, Remote Control Cable, Documentation Kit	
Optional Accessories	Interchangeable Lens Options (x7) T/R 0.38, T/R 0.9 - 1.2, T/R 1.2-1.56, T/R 1.5 - 2.0, T/R 2.0-4.0, T/R 4.0-7.0, T/R 6.9 -10.3	

* Note: Brightness specifications follow ISO 21118 standards and equal to ISO lumens

**Note: with Standard Lens

© 2023 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.