



**High Performance and versatile XGA short-throw portable projector with long-lamp and 3D Video Ready**

**Features**

- Bright 3,000 ANSI lumens of brightness for projection even in bright meeting rooms
- Crisp 15,000:1 contrast ratio ensuring clear presentations and sharp text
- Delivers a large 86" image from only 1m away from the projection surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Native XGA (1024 x 768) resolution up to maximum WUXGA (1,920 x 1,200)
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- 3D Ready via DLP® Link™ and HDMI v.1.4
- Audio ready with 2 watt audio speaker and audio-in/out ports
- Quiet operation with low 29dB (Eco mode) acoustic noise
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, security bar, and power button lock



Specifications		
<b>Display Type</b>	Single 0.55" DLP® Technology by Texas Instruments	
<b>Brightness (Typical)</b>	3,000 ANSI Lumens	
<b>Native Resolution</b>	XGA (1024 x 768) 4:3 format	
<b>Max. Resolution</b>	WUXGA (1920 x 1200) @60Hz	
<b>Contrast Ratio</b>	15,000:1	
<b>Lamp Life and Type</b>	5,000/7,000/10,000 Hours (Normal/Eco./Dynamic Eco), 210W	
<b>Throw Ratio</b>	0.63 (Distance/Width)	
<b>Image Size (Diagonal)</b>	60" to 300" (56" – 86" recommended for ST model)	
<b>Projection Distance</b>	2.35' – 3.61' (0.715m – 1.1m) based on 56" – 86" diagonal	
<b>Projection Lens</b>	F# 2.65, f=22.9mm	
<b>Zoom Ratio</b>	Fixed Lens	
<b>Aspect Ratio</b>	4:3 Native	
<b>Offset</b>	104%±5%	
<b>Keystone Correction</b>	± 40° Vertical	
<b>Horizontal Scan Rate</b>	15 - 102KHz	
<b>Vertical Scan Rate</b>	24 ~ 30Hz, 47 ~ 120Hz	
<b>3D Compatibility</b>	Yes; 3D (Via DLP® Link™, Blu-ray and Broadcast 3D)	
<b>Speaker</b>	2W	
<b>Remote Control</b>	Fully Featured IR Remote	
<b>Projection Method</b>	Table Top or Ceiling Mount (Front or Rear)	
<b>Uniformity</b>	85%	
<b>Computer Compatibility</b>	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible	
<b>Video Compatibility</b>	HDTV (1080i/p, 720p), SDTV(480i, 576i), EDTV (480p, 576p), SDTV(480i, 576i), NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM	
<b>I/O Connection Ports</b>	HDMI V1.4b (x2)	VGA-Out
	VGA-In (x2)	Audio-Out (Mini-Jack)
	S-Video	RS-232
	Composite Video	USB (Service Only)
	Audio-In (Mini-Jack)	
<b>Projection Method</b>	Table Top, Ceiling Mount (Front or Rear)	
<b>Security Solutions</b>	Kensington® Security Slot, Keypad Lock	
<b>Dimensions (WxDxH)</b>	331 x 244 x 105mm (13" x 9.6" x 4.1")	
<b>Weight</b>	2.6kg (5.7lbs)	
<b>Available Colors</b>	White (DX281ST)	
<b>Noise Level</b>	32dB/29dB (Normal/Eco. Mode)	
<b>Power Supply</b>	AC 100-240V, 50/60Hz	
<b>Power Consumption</b>	TBDW (Normal Mode), TBDW (Eco. Mode), <0.5W (Standby Mode)	
<b>Standard Accessories</b>	AC Power Cord, VGA Cable, Remote Control, Documentation Kit	
<b>Optional Accessories</b>	Wireless Collaboration System NovoPro, NovoDS, Lamp,	
<b>UPC</b>	813097023353	

