

3D DIGITAL PROJECTOR | H1060



Full HD 3D ready projector

The Vivitek H1060 is a Full HD entry level digital projector for Home Theater that features 3000 lumens, a 15,000:1 contrast ratio and DLP®/BrilliantColor™ technologies to deliver crisp, and vibrant images. With 3D-ready via DLP Link™, the H1060 can display 3D sources, such as, a 3D Blu-Ray™ player or broadcast 3D. Built with true HD 1080p widescreen resolution, enhanced color performance and HDMI v1.4, the Vivitek H1060 is the right choice for the latest video content.

Features

- Full high definition 1080p (1920x1080) resolution
- 3000 lumens of brightness and a 15,000:1 contrast ratio
- High-efficiency lamps that last up to 10,000 hours (in Dynamic Eco mode)
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- DLP/BrilliantColor™ technology by Texas Instruments
- Six segment color wheel for outstanding color reproduction
- 3D-Ready via DLP® Link™, Full 3D From Blu-Ray™ or broadcasted via cable or satellite
- Audio ready with built-in 2 watts audio speaker
- Audio-in and Audio-out ports
- RS-232c for integration and system administration compatible with Crestron, AMX, and Extron
- Top-loading cover for quick and easy lamp replacement
- Keypad lock feature to avoid accidental change to the setting
- Compatible with long VGA cables for a maximum length up to 20 meters

| Specifications | | |
|------------------------|---|-------------------------|
| Brightness | 3000 Lumens | |
| Native Resolution | 1080p (1920 x 1080) | |
| Contrast Ratio | 15,000:1 (Full On/Off) | |
| Lamp Life and Type | 5,000/6,000/10,000 (Normal/Eco/Dynamic Eco Mode), 190W | |
| Lamp Part # | 5811118154-SVV | |
| Display Type | Single 0.65" DC3 DMD DLP® Technology by Texas Instruments | |
| Throw Ratio (±3%) | 1.14 to 1.5:1 (Distance/Width) | |
| Image Size (Diagonal) | 30.1" to 317" (0.78 to 9.40m) | |
| Projection Distance | 3.287' to 26.24' (1 to 8m) | |
| Projection Lens | F= 2.59 - 2.91, f= 16.87 - 21.87mm | |
| Zoom Ratio | 1.3:1 Manual Zoom/Focus | |
| Aspect Ratio | 16:9 Native , 4:3 Compatible | |
| Offset | 115% | |
| Keystone Correction | ±40° Vertical | |
| Color Spectrum | 1.07 Billion | |
| Horizontal Scan Rate | 2D: 15, 30 to 91.4KHz/ 3D: 101.6 KHz | |
| Vertical Scan Rate | 24~30, 47~ 120 Hz | |
| Speaker | 2 Watt Mono | |
| Remote Control | Name Card-Type IR Remote | |
| Projection Method | Table Top or Ceiling Mount (Front or Rear) | |
| Uniformity | 95% | |
| Computer Compatibility | WUXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible | |
| 3D Ready | Yes (DLP® Link™, Full 3D from Blu-Ray or broadcasted via cable or satellite) | |
| 2D Video Compatibility | SDTV(480i, 576i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM | |
| I/O Connection Ports | HDMI v1.4 (x2) | HDMI 1/MHL Audio-In |
| | | HDMI 2 Audio-Out |
| | VGA-In | 3D-Sync Out |
| | RS-232 | Mini-USB (Service Only) |
| Security | Kensington® Lock Port. Keypad Lock | |
| Weight | 5.1lbs (2.3 kg) | |
| Dimensions (W x H x D) | 10.8" x 3.94" x 8.35" (275 x 212 x 100) | |
| Noise Level | 34dB/31dB (Standard/Economy Mode) | |
| Power | Supply: AC 100-240V, 50/60Hz Consumption: 200W (Economy Mode), 240W (Standard Mode), 0.5W (Standby Mode) | |
| Operating Temperature | 41 to 104°F (5 to 40°C) | |
| Warranty | 3-Year Limited Parts/Labor, 1-Year on Lamp | |
| Standard Accessories | AC Power Cord, VGA Cable, HDMI Cable, Remote Control with Battery User's Manual (CD) Warranty Card | |
| UPC | 813097021625 | |

