

True 86" 4K interactive display with wireless collaboration and touch interaction



Features

Hardware

- UltraHD 4K (3,840 × 2,160) resolution for outstanding details and stunning visuals
- 3mm-thick toughened glass for added protection against scratches or screen damage
- Front bezel USB-A, USB-C ports for quick connection to USB keyboards/mice, memory drives and data
- High-speed Wi-Fi 6 connection
- Dual RJ45 ports for easy Ethernet expansion
- Top-mounted 2.2CH speakers and 8-microphones array for video conferencing.

Software

- Google EDLA certified, Supporting multi-user profiles
- Writing double colors with dual pens simultaneously.
- Built-in whiteboard and NovoConnect screen sharing Apps to facilitate efficient collaboration in meeting rooms and classrooms
- Screen annotation and recording tools available for easy content sharing
- Centralized device management through Remote Manager Cloud or Windows software, simplifying IT administratio

Display	Type/Technology		Backlit D-LED (VA Panel)
	Panel Size		86"
	Brightness (Typ)		400cd/m2
	Contrast Ratio (Typ)		4,000:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Response Time (MS)		8ms (Typ)
	Refresh Rate (Hz)		60Hz
	Estimated Life Time (Typ)		30,000 hours (Min)
	Display Color (Bit)		1.07 billion (10-bit)
	Installation Orientation		Landscape
	Daily Operation (Hours/Days)		16/7
	Technology		Infrared Touch
Interactivity	Touch Points	Writing	10 Point (Standard)
		Touch	50 Point (Standard)
	Accuracy	Finger	±1mm (Over 90% area)
		Passive Pen	±1mm (Over 90% area)
	Response Time		<2.5ms
	Touch Resolution		32,768 x 32,768
	Surface Protection		3mm Anti-Glare Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
	Touch Tools		Finger, Stylus, Glove, Opaque Objects
Operating System	Anti-Palm		Supported
	System Version		Android™ v13.0
	CPU		Qcta-Core High-Performance ARM®CPU
	GPU		Mali™ G610 MP4
	RAM		8GB DDR5
Connectivity	Internal Storage		64GB (eMMC Flash) (About 25GB User Availability)
	Input	Display	HDMI v2.0 (x3) Side HDMI v2.0 (x1) Front DP v1.4&v2.3 (x1) Bottom USB-C (x1) Side
		Audio	Mic(3.5mm)(x1)
	Output	Display	HDMI-Out v2.0 (x1) (up to 4K@60Hz) USB-C (x1) (up to 4K@60Hz)
		Audio	Line-Out (3.5mm) (x1), SPDIF-Out (x1)
	Internet		LAN (RJ45) (10/100/1000 Mbps) (x2)
	Control		RS232-In (x1)
	Wireless	WiFi	IEEE802.11ax (2.4GHz/5GHz)
		Bluetooth	BT 5.2
		I/R Receiver	Front (x1) (±25° Angle, >8m Distance)
	USB-A	Front	USB 3.0 (x2)
		Side	USB 3.0 (x2)
		Bottom	USB 2.0 (x1, For system upgrade)
	USB-B	Side	USB Type B (x1) (For HDMI Input Touch Port)
		Side	USB Type B (x1) (For DisplayPort Touch Port)
	USB-C	Front	USB-C in(x1) (up to PD 20V/5A charging, display input)
		Bottom	USB-C in(x1) (up to PD 5V/3A charging, display output) USB-C Out (x1)
Expansion	OPS Slot		Standard Intel 80pin OPS
	Speakers		2x8W + 2x18W (2.2CH, Top-mounted)
Audio	Microphones		8-microphone array (Pickup radius: 8M)
	Power Supply (Internal)		AC 100 - 240V, 50/60Hz (6.0A)
Power	Consumption		≤375W
	Standby Mode		≤0.5W (Standby)
Physical Characteristics	VESA Mounting (FPMPI)		800 x 600mm M8x25(mm)
	Dimension (L x H x D)		1,957 x 1,171 x 86 mm (77.1" x 46.1" x 3.4")
	Weight		63.6kg (140lbs)
	Color		Gray
	Accessories		AC Power Cord, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, HDMI Cable(3M), Touch Cable(3M) Documentation Kit
Accessories	Standard		
	Optional		Windows OPS Module – Standard 80pin