



Bright and Light, ultra compact HD projector

The Qumi Q4, the next generation of Vivitek's series of HD LED pocket projectors, has a brightness level up to 500 lumens and weighs only 1.1 pounds. The Qumi Q4 features a DLP® Pico chipset and BrilliantColor™ technologies from Texas Instruments full connectivity options allows it to be used with a variety of other portable devices, including, but not limited to smart phones, laptops, tablets, digital and video cameras. Versatile and portable, the Vivitek Qumi Q4 is perfect for sharing digital content at work and play.

Features

- Native WXGA native resolution, HD 720p compatible resolution
- Up to 500 lumens of brightness and 30,000:1 contrast
- Estimated 30,000 hours of operation
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Connectivity options include: HDMI, Universal I/O for VGA, AV-In (Composite and audio input), Audio-out
- 3D-Ready via DLP Link
- Quick search source filtering function to quickly locate input signal source
- Intuitive and easy-to-use user interface makes projector adjustments a snap
- Embedded Closed Caption Decoding (CCD) ensures a video or TV signal's audio is displayed as subtitles (captions) on the projected screen
- 6 preset display modes and 3 user defined modes allow the projected image to be set for the most suitable display requirements depending on content and environment.
- Only 1.1 pounds . Chassis color is black.



Specifications		
Brightness	Up to 500 Lumens	
Native Resolution	WXGA (1280 x 800)	
Max. Resolution	UXGA (1600 x 1200)	
Contrast Ratio	30,000:1 (Full On/Full Off)	
Light Source Life and Type	≈30,000 Hours, LED	
Display Type	HD Pico DLP Technology by Texas Instruments	
Throw Ratio (±3%)	1.55:1 (Distance/Width)	
Image Size (Diagonal)	30" to 90" (0.8 to 2.3 m)	
Projection Distance	3.3' to 9.9' (1.0 to 3.0 m)	
Zoom Ratio	Fixed Lens, Manual Focus	
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible	
Offset	102.5%	
Keystone Correction	± 40° Vertical	
Color Spectrum	1.07 Billion	
Horizontal Scan Rate	15, 30 to 90 KHz	
Vertical Scan Rate	43 to 85 Hz	
Speaker	N/A	
Projection Method	Table Top, Tripod (¼ - 20) or Ceiling (Front or Rear)	
Uniformity	85%	
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible	
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM	
I/O Connection Ports	HDMI 1.4b + MHL 2.1 (x1) Universal I/O (24-Pin Connector for VGA/Component Input) AV-In (mini-jack) for Composite video and Audio Audio-Out (mini-jack) USB (service only)	
Weight	17.3 oz (1.1 lbs)	
Dimensions (W x H x D)	6.3" x 1.3" x 4.03" (162 x 32.3 x 102.4 mm)	
Noise Level	37dB/32dB (Standard / Eco Mode)	
Power	Supply: AC 100-240V, 50/60Hz Consumption: 62W (Boost Mode), <0.5W (Standby)	
Operating Temperature	41 to 95 °F (5 to 35 °C)	
Warranty	2-Year Limited Parts and Labor	
Standard Accessories	Power Adapter	Warranty Card
	Remote Control	Quick Start Guide
	24-pin Universal I/O to VGA Cable	
Optional Accessories	3.5mm AV-in Cable	
	HDMI Cable	
UPC	8813097020208 (Black/Q4-BK)	

