

PORTABLE PROJECTOR

DH268-WH



Full HD 1080P High Performance Widescreen portable projector with 3D Video Ready

Features

- Brilliant 1080p (1,920 x 1,080) projection with a maximum WUXGA (1,920 x1,200) resolution
- Bright 3,500 ANSI lumens of brightness for projection even in bright meeting rooms
- High 15,000:1 contrast ratio ensuring clear presentations and sharp text
- DLP® and BrilliantColor™ technologies for distinct and vibrant images
- Low cost of ownership and maintenance with an energy efficient lamp for up to 10,000 hours (Dynamic Eco. Mode) of usage
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- Extensive connectivity inputs and outputs including HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, and USB (Service)
- Manual zoom and focus for easy adjustment and positioning flexibility
- Audio ready with 2 watt audio speaker and audio-in/out ports
- Quiet operation with low 29dB (Eco mode) acoustic noise
- Top sided lamp cover for simple lamp removal and insertion
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, security bar, and power button lock









| Specifications Display Type Single 0.65" DLP® Technology by Texas Instruments Brightness (Typical) 3,500 ANSI Lumens Native Resolution 1080p (1920 x 1080), 16:9 format | | |
|---|--|--|
| Brightness (Typical) 3,500 ANSI Lumens | | |
| | | |
| Native Resolution 1080p (1920 x 1080), 16:9 format | | |
| 1555p (2525 / 2555) 15111dt | | |
| Max. Resolution WUXGA (1920 x 1200) @60Hz | WUXGA (1920 x 1200) @60Hz | |
| Contrast Ratio 15,000:1 | 15,000:1 | |
| Lamp Life and Type 5,000/7,000/10,000 Hours (Normal/Eco./Dynamic Education) | 5,000/7,000/10,000 Hours (Normal/Eco./Dynamic Eco), 210W | |
| Throw Ratio (±3%) 1.28 – 1.56:1 (Distance/Width) | 1.28 – 1.56:1 (Distance/Width) | |
| Image Size (Diagonal) 60" to 300" | 60" to 300" | |
| Projection Distance 4′ – 25.2′ (1.2m – 7.7m) | 4' – 25.2' (1.2m – 7.7m) | |
| Projection Lens F# 2.42 – 2.62, f=19.0 -22.65mm | | |
| Zoom Ratio 1.2x Manual Zoom/Focus | | |
| Aspect Ratio 16:9 Native, 4:3 Compatible | | |
| Offset 106.4%±5% | 106.4%±5% | |
| Keystone Correction ± 40° Vertical | ± 40° Vertical | |
| Horizontal Scan Rate 15 - 102KHz | 15 - 102KHz | |
| Vertical Scan Rate 24 ~ 30Hz, 47 ~ 120Hz | 24 ~ 30Hz, 47 ~ 120Hz | |
| 3D Functionality Full 3D (Via DLP® Link™, Blu-ray and Broadcast 3D) | Full 3D (Via DLP® Link™, Blu-ray and Broadcast 3D) | |
| Speaker 2W | 2W | |
| Remote Control Fully Featured IR Remote | Fully Featured IR Remote | |
| Projection Method Table Top or Ceiling Mount (Front or Rear) | Table Top or Ceiling Mount (Front or Rear) | |
| Uniformity 85% | 85% | |
| Computer Compatibility WUXGA, UXGA,WXGA, SXGA+, SXGA, XGA, SVGA, VG VESA Standards; PC and Macintosh Compatible | WUXGA, UXGA,WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible | |
| | HDTV (1080i/p, 720p), SDTV(480i, 576i), EDTV (480p, 576p), SDTV(480i, 576i), NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM | |
| HDMI V1.4b (x2) VGA-Out | | |
| VGA-In (x2) Audio-Out (Mini-Jac | ck) | |
| I/O Connection Ports S-Video RS-232 | • | |
| Composite Video USB (Service Only) | | |
| Audio-In (Mini-Jack) | | |
| Projection Method Table Top, Ceiling Mount (Front or Rear) | | |
| Security Solutions Kensington® Security Slot, Keypad Lock | Kensington® Security Slot, Keypad Lock | |
| Dimensions (WxDxH) 331 x 244 x 105mm (13" x 9.6" x 4.1") | 331 x 244 x 105mm (13" x 9.6" x 4.1") | |
| Weight 2.6kg (5.7lbs) | 2.6kg (5.7lbs) | |
| Available Colors White (DH268-WH) | White (DH268-WH) | |
| Noise Level 32dB/29dB (Normal/Eco. Mode) | 32dB/29dB (Normal/Eco. Mode) | |
| | AC 100-240V, 50/60Hz | |
| | TBDW (Normal Mode), TBDW (Eco. Mode), <0.5W (Standby | |
| Standard Accessories AC Power Cord, VGA Cable, Remote Control, Docu | AC Power Cord, VGA Cable, Remote Control, Documentation Kit | |
| Optional Accessories Wireless Collaboration System NovoPro, NovoDS, La | ımp, | |
| UPC 813097023346 | | |













