

Multimedia Projector

# Vivitek DH976-WT

High performance, high brightness 1080p multimedia projector



Features

- Full high definition 1080p (1920x1080) resolution with 4,800 ANSI lumens and a 15,000:1 contrast ratio
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- Vertical lens shift and 1.5x zoom range for flexible image sizing and distance planning
- 5 segment RYGBW color wheel for improved and vivid color reproduction
- Assortment of video (HDMI 1.4b, DisplayPort, VGA, S-Video, Composite Video), communication (RJ45, USB, RS232, 12v trigger) and audio (audio-in/out) I/O options for simplified device connectivity
- Extend lamp life with an energy efficient lamp that deliver up to 4,000 hours of usage (Dynamic Eco. Mode)
- Project 3D content from DLP® Link™, BluRay HDMI 1.4b for realistic life-like images
- Built-in 3W audio speaker with multiple audio-in and audio-out ports
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Choice of 8 pre-set display scenario modes including presentation, bright, game, movie, TV, sRGB, blackboard and user
- Integrated Closed Caption Decoding (CCD) automatically converts the audio portion of a TV signal and displays it as subtitles on the projected screen
- Hassle-free maintenance with top loading lamp door for convenient lamp replacement
- Anti-theft security features include: Kensington® security slot, security bar, and password protected keypad lock
- 5 yr. Limited Parts and Labor warranty, 3 yr. Advanced Exchange, 1 yr. lamp warranty or 1,500 hours.

Specifications

Display Type	Single 0.65" DLP Technology by TI
Brightness	4,800 ANSI Lumens
Native Resolution	1080P (1920 x 1080)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	15,000:1
Lamp Life/Type	2500/3500/4000 Hours (Normal /Eco/Dynamic Eco Mode) 310W/245W
Throw Ratio	1.39 - 2.09
Image Size (Diagonal)	25.9" - 324.9"
Projection Distance	1.2m - 10m (3.97' to 32.8')
Projection Lens	F/#2.42 - 2.97, f=20.9 - 31.05
Zoom Ratio	1.5x
Aspect Ratio	16:9 Native
Offset (Vertical)	111% ±5% ~ 131% ±5%
Keystone Correction	Vertical ±30°
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Lens Shift Shif	Yes (Vertical/Manual)
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	3W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (x2), HDMI v1.4 (x2), DisplayPort, S-Video, Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, 3D-Sync-Out, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	332.8 x 255 x 114.6mm (13.1" x 10" x 4.5")
Weight	3.95kg (8.7lbs)
Available Color	White
Noise Level	36dB/30dB (Normal/Eco. Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	370W (Normal Mode), 300W (Eco. Mode), <0.5W (Standby Mode) , <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Carry Case, Documentation Kit
Optional Accessories	Replacement Lamp

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

Photos

