



Spotlight the Presentation

The Vivitek D508 and D509 SVGA/XGA digital projectors offer 2600 lumens of brightness, 3000:1 contrast ratio and DLP® and BrilliantColor™ technologies for sharp, detailed images. With a variety of functions and features, the Vivitek D508/D509 will put your presentation in the spotlight.

Features

- Native SVGA/XGA resolution and displays up to UXGA
- DLP and BrilliantColor technologies by Texas Instruments
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- Keypad lock feature to avoid accidental changes to the setting
- Closed-caption and rapid on/off feature
- Enhanced color and display adjustments

Specifications	
Brightness	2600 Lumens
Native Resolution	D508: SVGA (800 x 600) D509: XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	≈3000/4000 Hours (Standard/Economy Mode), 180W
Lamp Part #	5811116320-S
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio (±3%)	1.92 to 2.14:1 (Distance/Width)
Image Size (Diagonal)	40" to 300" (1.0 to 7.6 m)
Projection Distance	5.1' to 42.8' (1.6 to 13.0 m)
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95 mm
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	128%
Keystone Correction	±30° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	2 Watt Mono
Remote Control	Card-Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	VGA-In, Composite Video, S-Video, RCA Stereo Audio-In, Mini-Jack Audio-In, RS232c
Security	Kensington® Lock Port
Weight	4.2 lbs (1.9 kg)
Dimensions (W x H x D)	10.3" x 3.0" x 7.5" (261 x 78 x 190mm)
Noise Level	31dB/28dB (Standard/Economy Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 205W (Economy Mode), 230W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Parts/Labor, 90-Day Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, Warranty Card
UPC	8 14964 33561 6/8 14964 33562 3 (D508/D509)

