

Portable Projector

Vivitek DS234

Versatile and value-oriented SVGA projector



Features

- DLP® and BrilliantColor™ technologies for the ultimate in picture quality
- Bright 3,200 ANSI lumens and high 10,000:1 contrast ratio ensures a crisp and sharp image
- Native SVGA (800 x 600) resolution with display up to 1080p (1920 x1080)
- Energy efficient lamp that delivers up to 8,000 hours (Dynamic Eco. Mode) of usage
- 5 segment WBRYG color wheel for improved and vivid color reproduction
- 3D-Ready via DLP® Link™ and HDMI v.1.4a technology
- Audio ready with 2 watt audio speaker and audio-in/out ports
- Quiet operation with low 28dB (Eco mode) acoustic noise
- Source filtering function to save time locating device signal source
- Choice of 6 pre-set display scenario modes including: presentation, sRGB, cinema, dynamic, user 1 and user 2
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 1.97kg (4.32lbs)
- Anti-theft security features include: Kensington® Security Slot, security bar, and power button lock

Specifications

<u> </u>	
Display Type	Single 0.55" DLP® Technology by TI
Brightness	3,200 ANSI Lumens
Native Resolution	SVGA (800 x 600)
Maximum Resolution	1080p (1920 x 1080)
Contrast Ratio	10,000:1
Lamp Life/Type	4,500/6,000/8,000 Hours
	(Normal/Eco./Dynamic Eco), 203W/170W
Throw Ratio	1.97 - 2.17:1
Image Size (Diagonal)	27" - 290" (68.58 – 736.6cm)
Projection Distance	1.2 - 11m (3.93ft - 36.1ft)
Projection Lens	F=2.51 - 2.69, f=21.95mm - 24.18mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native
Offset	115 ±5%
Keystone Correction	Vertical ±40°
Horizontal Frequency	31 - 100kHz
Vertical Frequency	50 - 120Hz
3D Functionality	Yes (Supports DLP® Link™, HDMI v.1.4)
Speaker	2W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA,
	UXGA, Mac
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p),
	HDTV (720p, 1080i/p), NTSC, PAL,
	SECAM
I/O Connection Ports	HDMI v1.4a, VGA-In, Composite-In,
	Audio-In (Mini-Jack), Audio-Out (Mini-
	Jack), RS-232, USB (Mini-Type B
	(Service))
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar,
	Power Button Lock
Dimensions (W x D x H)	285 x 193.5 x 111.5mm (11.2" x 7.6" x 4.4")
Weight	1.97kg (4.32lbs)
Available Color	Black
Operating Temperature	5° - 40°C
Noise Level	30dB/28dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	220W (Eco. Mode), 260W (Normal Mode),
·	<0.5W (Standby) AC Power Cord, VGA Cable, Remote
Standard Accessories	Control w/Batteries, Documentation Kit
	Replacement Lamp, Bag, Filter
Optional Accessories	
©2015 Vivitek, Vivitek is a trademark of Delta Electronics, Inc. Other trademarks	

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.







Photos







