

NovoTouch

NovoTouch EK655i

True 65" 4K interactive display with wireless collaboration and touch interaction for the classroom



Features

- 65" display with ultraHD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- Backlit D-LED (IPS panel) technology for brighter pictures, flawless colors, richer textures, and extra wide viewing angels (178°/178°)
- Preconfigured with NovoConnect wireless presentation and collaborative system for cable-free and hassle-free presenting in the classroom
- Connect up to 64 users simultaneously, and allow 4 . people to present on one display to facilitate large group work
- Optional LauncherPlus wireless dongle connects to . any visitor's laptop for a direct plug-n-play WiFi connection without impacting an existing network
- High contrast ratio and fast response time . deliverables crisp, readable content
- Interactive functionality with up to a 20-point finger touch capabilities (10-point writing, 20-point touch) for on-screen annotation, drawing and common gesture controls
- Simple wireless display and true fast collaboration solution thanks to WiFi 6, 802.11AX dual-band 2.4/5GHz support
- Provide API or Remote Manager with IT management software with automatic discovery and configuration
- Full suite of connectivity ports including HDMI-In VGA-In, Audio-In/Out, LAN, RS232 and USB.
- Front bezel USB 3.0 ports for quick connection to USB memory drives and data
- 4mm thick toughened glass for added protection . against scratches or screen damage
- Support HDMI-IN on presentation or digital signage mode
- Built-in NovoDS capability as an all-in-one digital signage solution, easy to set up and manage via Windows/Mac software or NovoDS.com Cloud service
- Daily auto-reboot and low blue light support
- VESA compliant mounting for easy installation
- Powerful front- facing stereo audio speakers with up to 32W of total power (16Wx2) and multiple audioin/out ports

	Type/Technology		Backlit D-LED (IPS Panel)
	Panel Size		65"
	Brightness (Typ)		350cd/m2
	Contrast Ratio (Typ)		5,000:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
Display	Aspect Ratio		16:9
	Response Time (MS)		6.5ms (Typ)
	Refresh Rate (Hz)		60Hz
	Estimated Life Time (Typ)		30,000 hours (Min)
	Display Color (Bit)		1.07 billion (10-bit)
	Installation Orientation		Landscape
	Daily Operation (Hours/Days)		16/7
	Technology		Infrared Touch
		Writing	10 Point (Standard)
Interactivity	Touch Points	Touch	20 Point (Standard)
	Accuracy	Finger	±1.0mm (Over 90% area)
		Passive	
		Pen	±1.0mm (Over 90% area)
	Response Time		≤ 10ms
	Touch Resolution		32,768 x 32,768
			4mm Thick Toughened Glass (Level 7H on
	Surface Protection		Mohs Scale of Mineral Hardness)
	Touch Tools		Finger, Stylus, Glove, Opaque Objects
	System Version		Android™ v9.0 (upgrade to v11.0)
	CPU		Multi-Core High-Performance ARM [®] CPU
Operating	GPU		4*Mali™ G52
System	RAM		8GB DDR3
	Internal Storage		64GB (eMMC Flash)
		6	HDMI v2.0 (x3) (HDCP v2.2 Compliant)
	Input Output	Display	USB Type C (x1)
		Display	VGA-In (x1)
		Audio	Audio-In (3.5mm) (x1)
		Display	HDMI-Out v1.4(x1)-1080P@60Hz (option)
			Audio-Out (3.5mm) (x1)
	output	Audio	
		Audio	SPDIF-Out (x1)
	Internet Control	Audio	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2)
O	Internet		SPDIF-Out (x1)
Connectivity	Internet Control	Audio Wifi (USB Module)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1)
Connectivity	Internet		SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax
Connectivity	Internet Control	Wifi (USB Module)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0
Connectivity	Internet Control	Wifi (USB Module) Bluetooth	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz)
Connectivity	Internet Control	Wifi (USB Module) Bluetooth I/R Receiver	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance)
Connectivity	Internet Control Wireless	Wifi (USB Module) Bluetooth I/R Receiver Front	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2)
Connectivity	Internet Control	Wifi (USB Module) Bluetooth I/R Receiver	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2)
Connectivity	Internet Control Wireless	Wifi (USB Module) Bluetooth I/R Receiver Front	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB 3.0 (x2) USB 3.0 (x2) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port)
Connectivity	Internet Control Wireless USB	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1)
	Internet Control Wireless USB Window Modu	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option)
Connectivity	Internet Control Wireless USB Window Modu Speakers	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo)
Audio	Internet Control Wireless USB Window Modul Speakers Power Supply	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A)
	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A)
Audio	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L x 1	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L x1 Weight	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×I) Weight VESA Mountin	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby) 1,488 x 897 x 86mm 41.4kg 4 - M6 × 25mm, 600 x 400mm
Audio Power Physical Characteristics	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×I) Weight VESA Mountin Color	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby) 1,488 x 897 x 86mm 41.4kg 4 - M6 × 25mm, 600 x 400mm Grey
Audio Power Physical	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×I) Weight VESA Mountin	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby) 1.488 x 897 x 86mm 41.4kg 4 - M6 × 25mm, 600 x 400mm Grey Lighting Sensor
Audio Power Physical Characteristics	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×I) Weight VESA Mountin Color	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1 Weight VESA Mountin Color Built-in	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×I) Weight VESA Mountin Color	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-In (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics Sensor	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1 Weight VESA Mountin Color Built-in	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1 Weight VESA Mountin Color Built-in	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics Sensor	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1) Weight VESA Mountin Color Built-in Standard	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics Sensor	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1 Weight VESA Mountin Color Built-in	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)
Audio Power Physical Characteristics Sensor	Internet Control Wireless USB Window Modu Speakers Power Supply Consumption Standby Mode Dimension (L×1) Weight VESA Mountin Color Built-in Standard	Wifi (USB Module) Bluetooth I/R Receiver Front Side Bottom le (Option) (Internal)	SPDIF-Out (x1) LAN (RJ45, 10/100/1000M) (x2) RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (4.0A) 400W <0.5W (Standby)

©2022 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

