

Vivitek D518

Ultra mobile digital projector for brilliant presentations



Product Features

- Native SVGA resolution with 15,000:1 contrast ratio
- 3D-ready via DLP® Link™ for games and movies
- High-efficiency lamps that last up to 6,000 hours
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- RS-232c for projector control and management
- Connectivity options including: HDMI v1.3, VGA-In, S-Video, Composite Video, and RS-232C
- Keypad lock prevents accidental system adjustments
- Closed caption and rapid on/off feature
- Lightweight at only 1.9kg

Product Photos









Product Specifications	
Display Type	Single 0.55" DLP® Technology by TI*
Brightness	3000 ANSI Lumens
Native Resolution	SVGA (800 x 600)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	15,000:1
Lamp Life and Type	4,000 / 6000 Hours (Boost / Std. Mode), 190W
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	40" - 300"
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native
Offset	128%
Keystone Correction	Vertical +/-30
Horizontal Frequency	15, 30 - 90kHz
Vertical Scan Rate	43 - 85Hz
Speakers	2W (Mono)
3D Ready	Yes (Via DLP Link)
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K,
	K1, L)
I/O Connection Ports	HDMI v1.3, VGA-In, S-Video, Composite
	Video, Audio-In RCA (L/R), Audio-In
	(Mini-Jack), RS-232C
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar,
	Keypad Lock
Dimensions (W x D x H)	261 x 190 x 78mm (10.33" x 7.8" x 3")
Weight	1.9kg (4.2lbs)
Noise Level	30dB/33dB (Std. / Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	230W (Eco. Mode), 260W (Std. Mode), <1W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case

©2013 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.











