

PORTABLE DIGITAL PROJECTOR

D552



The Vivitek D552 digital projector features SVGA resolution, 3000 lumens of brightness, 15,000:1 contrast ratio and DLP®/BrilliantColor™ technologies for sharp, detailed images. With high-efficiency lamps that go up to 6000 hours, as well as enhanced color and display adjustments, the Vivitek D552 delivers picture-perfect imagery that lasts. Weighing in at 5.1 pounds and with a built-in speaker, the D552 is picture perfect portable presenter.

Features

- Native SVGA resolution and displays up to WUXGA
- High-efficiency lamps that last up to 6,000 hours (in Eco mode)
- DLP and BrilliantColor technologies by Texas Instruments
- Connectivity with dual VGA inputs (component capability), VGA output, Composite Video and S-Video
- Video Auto Gain Control to Enhance Color Performance
- RS-232C
- Top-loading cover for quick and easy lamp replacement
- Closed captioning and rapid on/off feature
- Keypad lock feature to avoid accidental change to the setting











Specifications	
Specifications	2000
Brightness	3000 Lumens
Native Resolution	SVGA (800 x 600)
Max. Resolution	WUXGA (1600 x 1200)
Contrast Ratio	15,000:1 (Full On/Off)
Lamp Life and Type	5000/6000 Hours (Normal/Eco Mode), 190W
Lamp Part #	5811118154-SVV
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio (±3%)	1.92 to 2.14:1 (Distance/Width)
Image Size (Diagonal)	23" to 256" (1.0 to 7.6 m)
Projection Distance	3.28' to 32.8' (1 to 10 m)
Projection Lens	F = 2.52-2.73, f = 21.8~24mm
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	128%
Keystone Correction	±40° Vertical, ±40 steps
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 91.4KHz / 3D: 101.6KHz
Vertical Scan Rate	24-30Hz, 47 to 120Hz
Speaker	2 Watt Mono
Remote Control	Card-Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	95%
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N),
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
I/O Connection Ports	VGA-In (x2), VGA-Out, Composite Video, S-Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, RS-232c, Mini-USB (Service)
Security	Kensington® Lock Port
Weight	5.1lbs (2.3 kg)
Dimensions (W x H x D)	10.8" x 8.35" x 3.94" (275 x 212 x 100)
Noise Level	35dB/32dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 200W (Eco Mode), 240W (Normal Mode), 0.5W (Standby Mode)
Operating Temperature	41 to 95°F (5 to 35°C)
Warranty	3-Year Limited Parts/Labor, 1-Year on Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, User's Manual (CD), Warranty Card
UPC	814964 338006