

Qumi Q2-Lite



Bright and Lightweight, HD- and 3D-Ready

The Qumi Q2, Vivitek's innovative LED pocket projector, just got simpler. Still weighing in at 1.1 pounds and having a brightness level up to 300 lumens, the Q2-Lite has multiple connectivity options allowing it to be used with a variety of devices. The Q2-Lite is 3D-ready via DLP® Link™ and features a DLP Pico chipset and BrilliantColor™ technologies from Texas Instruments. With the combination of versatility, portability and a sleek design, the Vivitek Q2-Lite is perfect for sharing digital content at work and play.

Features

- Native HD 720p resolution
- Up to 300 lumens of brightness
- Estimated 30,000 hours of LED operation
- 3D-Ready via DLP Link
- Presentation Timer
- Enhanced color and display adjustments for wall color correction
- Connectivity options: Mini-HDMI, Universal I/O, AV mini-jack, mini-jack audio-out
- Only 1.1 pounds and available in black or white finish

Specifications	
Brightness	Up to 300 Lumens
Native Resolution	HD 720p
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	10,000:1 (Full On/Full Off)
Lamp Life and Type	≈30,000 Hours, LED
Display Type	HD Pico DLP Technology by Texas Instruments
Throw Ratio (±3%)	1.55:1 (Distance/Width)
Image Size (Diagonal)	30" to 90" (0.8 to 2.3 m)
Projection Distance	3.3' to 9.9' (1.0 to 3.0 m)
Zoom Ratio	Fixed Lens, Manual Focus
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	102.5%
Keystone Correction	± 15° Vertical (+/- 40 steps)
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Projection Method	Table Top, Tripod (¼ - 20) or Ceiling (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	Mini-HDMI, Universal I/O (24-Pin Connector for VGA/Component Input), AV Mini-Jack, Mini-Jack Audio-Out, USB (Service only)
Weight	17.3 oz (1.1 lbs)
Dimensions (W x H x D)	6.3" x 1.3" x 4.0" (160 x 32 x 102 mm)
Noise Level	28dB/32dB (Standard / Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 65W (Boost Mode), <0.5W (Standby)
Operating Temperature	41 to 95 °F (5 to 35 °C)
Warranty	1-Year Limited Parts/Labor
Standard Accessories	Power Adapter, Universal I/O to VGA Cable, Remote Control
UPC	814964 337030 (White), 814964 337023 (Black)

