

# Vivitek D519

Ultra mobile digital projector for brilliant presentations



## Product Features

- High 15,000:1 contrast with 3000 ANSI lumens
- Native XGA resolution and displays up to UXGA
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 6,000 hours (in standard mode)
- 3D-ready via DLP® Link™
- Built-in enhanced color and display adjustments
- Connectivity options including: HDMI v1.3, VGA-In, S-Video, Composite Video, and RS-232C
- Keypad lock prevents accidental system adjustments
- Closed caption and rapid on/off feature
- Great portability at 1.9kg

## Product Photos



| Product Specifications |  |
|------------------------|--|
| Display Type           | Single 0.55" DLP® Technology by TI   |
| Brightness             | 3000 ANSI Lumens   |
| Native Resolution      | XGA (1024 x 768)   |
| Maximum Resolution     | UXGA (1600 x 1200)@60Hz  |
| Contrast Ratio         | 15,000:1   |
| Lamp Life and Type     | 4,000 / 6000 Hours (Boost / Std. Mode), 190W   |
| Throw Ratio            | 1.92 - 2.14:1  |
| Image Size (Diagonal)  | 40" - 300"   |
| Projection Distance    | 1 - 10m (3.28ft to 32.8ft)   |
| Projection Lens        | F = 2.52 - 2.73, f = 24.34 - 25.95mm   |
| Zoom Ratio             | 1.1x   |
| Aspect Ratio           | 4:3 Native   |
| Offset                 | 128%   |
| Keystone Correction    | Vertical +/-30   |
| Horizontal Frequency   | 15, 30 - 90kHz   |
| Vertical Scan Rate     | 43 - 85Hz  |
| Speakers               | 2W (Mono)  |
| 3D Ready               | Yes (Via DLP Link)   |
| Lens Shift Range       | N/A  |
| Video Compatibility    | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) |
| I/O Connection Ports   | HDMI v1.3, VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C   |
| Projection Method      | Table Top, Ceiling Mount (Front or Rear)   |
| Security Solutions     | Kensington® Security Slot, Security Bar, Keypad Lock   |
| Dimensions (W x D x H) | 261 x 190 x 78mm (10.33" x 7.8" x 3")  |
| Weight                 | 1.9kg (4.2lbs)   |
| Noise Level            | 30dB/33dB (Std. / Boost Mode)  |
| Power Supply           | AC 100-240V, 50/60Hz   |
| Power Consumption      | 230W (Eco. Mode), 260W (Std. Mode), <1W (Standby)  |
| Standard Accessories   | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit                               |
| Optional Accessories   | Replacement Lamp, Remote, Carrying Case  |

©2013 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

