

HOME CINEMA 4K PROJECTOR

HK2200

Ultra HD 4K projector for the Home Cinema enthusiast.

Features

- Ultra HD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- 2,000 ANSI lumens for an amazing brightness
- Extremely high 18,000:1 contrast ratio for spectacular blacks and outstanding white colors
- Advanced video processor for fluid video streaming and programmable RGB colour adjustments
- VividMotion reduces fast-moving motion judder to create a fluid and flawless video stream
- High Dynamic Range (HDR10) for enriched brightness and impeccable vibrancy for precise natural colors
- 100% REC 709 and 80% DCI-P3 for an incredible cinematic like movie experience
- Six segment RGBRGB color wheel delivers outstanding reds, greens and blue color reproductions
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Vertical len shift for greater installation convenience and flexibility
- Wirelessly screen casting capablity (Wifi USB dongle is required)
- Display content directly from projector's internal memory or flash drive
- Advanced HDMI 2.0 connectors for high quality digital video signals and quick data transfer rates
- Audio USB ready with built-in 5 watt speaker and audio out port
- Long lasting energy efficient lamps that last up to 15,000 hours (Dynamic Eco)
- Wide 1.3x zoom range and vertical lens shift for greater installation convenience and flexibility
- Full functioning remote control for easy control
- Secure a cable to the projector's security bar to prevent theft or unauthorized movement of the projector

Photos





Specifications		
Display Type	DLP® 0.47" TRP Technology by Texas Instruments	
Brightness (Typical)	2,000 ANSI Lumens	
Native Resolution	UHD (3840 2160), 16:9 Format	
Contrast Ratio	18,000:1 (Full On/Off)	
Lamp Life/Type	4,000 / 10,000 / 15,000 hours (Normal / Eco. / Dynamic Eco.)	
	245W	
Throw Ratio	1.13 – 1.47:1	
Image Size (Diagonal)	0.8 - 7.62 (30" - 300")	
Projection Distance	0.95m – 7.6m (3.1ft - 25ft)	
Projection Lens	F= 1.9 – 2.47, f=12 – 15.6mm	
Zoom Ratio	1.3x	
Aspect Ratio	16:9	
Offset	100%	
Lens Shift Range	Vertical: +10% / -5 of full image height	
Vertical Scan Rate	24 - 85Hz	
Horizontal Frequency	31 - 135kHz	
Video Compatibility	UHD 4K (3840 2160), HDTV (1080i/p, 720p), EDTV (480p, 576p)	
Computer Compatibility	UHD 4K, WUXGA, UXGA, SXGA+, SXGA, XGA, SVGA, VGA, Mac	
3D	Yes (Via DLP® Link™, Blu-ray 3D)	
Speaker	5W (Mono)	
Remote Control	Fully Featured IR Remote	
Projection Method	Table Top or Ceiling Mount (Front or Rear)	
Uniformity	85%	
I/O Connection Ports	HDMI 1 v2.0	Audio-Out (3.5mm Mini Jack)
	HDMI 2 v2.0	Audio-Out (S/PDIF)
	USB 3.0 Type A (5V / 1.5A)	RS-232
	USB 2.0 Type A (5V / 1.5A)	12-V Trigger
	Power (5V/1.5A) USB Type A	Service Only (USB Type B)
Security	Kensington® Lock Port, Security Bar	
Weight	9.3lbs (4.2kg)	
Dimensions (W x D x H)	14.6" x 10" x 5.1" (370 x 253 x 130mm)	
Noise Level	32dB / 29dB (Normal / Eco)	
Power	Supply: AC 100-240V, 50/60Hz	
	Consumption: TBA W/ TBAW (Normal/Eco)	
	<0.5W (Standby Mode)	
Operating Temperature	41 to 104°F (5 to 40°C)	
Warranty	3-Year Limited Parts/Labor	
Standard Accessories	AC Power Cord, HDMI Cable, Remote Control, Batteries for Remote, User Manual (CD), Warranty Card	
UPC	813097024558	
01303/024330		

©2019 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.











