

Vivitek D517

High brightness ultra mobile projector



Product Features

- DLP and BrilliantColor™ technologies by Texas Instruments
- Native XGA (1024 x 768) resolution
- 15,000:1 contrast ratio and 3000 ANSI lumens for dazzling images for amazing picture quality
- Built-in enhanced color and display adjustments
- Connectivity options including: VGA-In, S-Video, Composite Video and RS-232C
- Keypad lock prevents accidental system adjustments
- Closed caption and rapid on/off feature
- Great portability at 1.9kg

Product Photos



Product Specifications	
Display Type	Single 0.55" DLP® Technology by TI
Brightness	3000 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	15,000:1
Lamp Life and Type	4,000 / 6000 Hours (Boost / Std. Mode), 190W
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	40" - 300"
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native
Offset	128%
Keystone Correction	Vertical +/-30
Horizontal Frequency	15, 30 - 90kHz
Vertical Scan Rate	43 - 85Hz
Speakers	2W (Mono)
3D Ready	Yes (Via DLP Link)
Lens Shift Range	N/A
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	261 x 190 x 78mm (10.33" x 7.8" x 3")
Weight	1.9kg (4.2lbs)
Noise Level	30dB/33dB (Std. / Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	230W (Eco. Mode), 260W (Std. Mode), <1W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Dgdocumentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case

©2013 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

