

vivitek®

DU7095Z

Large Venue Laser

High Performance Large Venue Laser
Projector with an Unbeatable ROI and
Image Quality



The DU7095Z offers the next generation of advanced projection technology – laser – with impressively vivid colors and a high brightness of 6,500 ANSI lumens. Designed lamp-free, it provides a low cost of ownership, with minimal maintenance, and gives a stable, high-quality projection for up to 20,000 hours. The DU7095Z offers an immersive big-screen experience with an unbeatable return on investment.

Features

- Advanced laser phosphor light engine provides a superior brightness and color uniformity to create the most immersive, big-screen images
- Lamp-less design delivers up to 20,000 hours of operational time
- 6,500 ANSI lumens and a 20,000:1 contrast ratio
- REC 709 enables reproduction of HDTV colors as intended by content creators
- 360° (degree) installation for flexible installation in a wide variety of environmental conditions
- HDBaseT™ interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- Available in Black and White



www.vivitekusa.com

A brand of  DELTA



DU7095Z



SPECIFICATIONS

Display Type	Single Chip 0.67" DLP Technology by TI
Brightness	6,500 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200)
Maximum Resolution	WUXGA (1920 x 1200) @ 60Hz
Contrast Ratio	20,000:1
Laser Life/Type	Up to 20,000 hours (Laser Phosphor Light Engine)
Throw Ratio*	1.54 - 1.93:1
Image Size (Diagonal)*	36.1" - 300"
Projection Distance*	1.5 - 10m (4.92 - 32.8 ft)
Projection Lens*	F#2.0~2.09, f=22.84-28.61mm
Zoom Ratio*	1.25x
Aspect Ratio	16:10
Lens	Manual Focus/Zoom and Lens Shift
Keystone Correction	Horizontal ±30°, Vertical ±25°
Horizontal Frequency	15, 31-91.4 KHz
Vertical Scan Rate	24-30 Hz, 47-120 Hz
3D	Yes (DLP® Link™, HDMI v1.4 (Blu-ray 3D))
Lens Shift Range*	Vertical: -15% + 55%, Horizontal: -5% +5%
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)

I/O Connection Ports

HDMI v1.4b, MHL/HDMI 1.4b, DVI-D, Composite Video, Component (5 BNC) (RGBHV), 3D-Sync-In, VGA-In, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out RCA (L/R), 3D Sync-Out, USB Type A Power (5V/2.0A), RJ45, 12V Trigger, RS-232-In, RS-232-Out, Wired Remote-In, Wired Remote-Out, HDBaseT™, LAN, USB (Service)

Projection Method

Table Top, Ceiling Mount, Portrait (Front or Rear)

Security Solutions

Kensington® Security Slot, Security Bar, Keypad Lock

Dimensions (WxDxH)

18.5 x 20.3 x 7.9 in (470 x 517 x 202 mm)

Weight

24kg (52.9lbs)

Available Colors

Black (DU7095Z-BK)

White (DU7095Z-WH)

Noise Level

33dB/30dB (Normal/Eco. Mode)

Power Supply

AC 100-240V, 50/60 Hz; AC 100-240 V, 50/60 Hz

Power Consumption

650W (Normal Mode), 530W (Eco. Mode), <0.5W (Standby Mode), <3W (LAN Standby Mode)

Standard Accessories

AC Power Cord, VGA Cable, Remote Control, Documentation Kit

Optional Accessories

Interchangeable Lens Options (x7)

Warranty

5-Year Parts & Labor or 20,000 Hours (Whichever Comes First) and 3-Year Advanced Exchange Warranty

UPC Code

DU7095Z-WH: 813097023087

DU7095Z-BK: 813097023100

Model Number	VL904G/LNS-5FX2	VL911G/LNS-5WZ2	VL907G/LNS-5ST	VL912G/LNS-5SZ12	VL906G/LNS-5SZ12	VL908G/LNS-5LZ23	VL909G/LNS-5LZ2
Part Number	5811120818-SV	5811122742-SV	5811120054-SW	5811122743-SW	5811120865-SW	5811119237-SW	5811120055-SW
Lens Type	Wide Fixed	Short Zoom	Standard Short Zoom	Semi Short Zoom	Standard Zoom Lens	Long Throw Zoom 1	Long Throw Zoom 2
Throw Ratio	0.78:1	0.77 - 1.1:1	1.1 - 1.3:1	1.25 - 1.60:1	1.54 - 1.93:1	1.93 - 2.9:1	3.0 - 5.0:1
Zoom Ratio	N/A	1.42x	1.18x	1.28x	1.25x	1.5x	1.67x
f Value	11.46mm	11.45 - 16.32mm	16.64 - 19.54mm	18.65 - 23.85mm	22.84 - 28.61mm	28.5 - 42.75mm	44.5 - 74.19mm
F Number	2.54	2.1 - 2.6	2.05 - 2.27	2.0 - 2.44	2.0 - 2.09	2.5 - 3.1	2.2 - 2.5
Image Size	47.8" - 298.3"	42.3" - 300"	35.8" - 379.8"	39.1" - 300"	36.1" - 300"	32.1" - 481.1"	27.9" - 309.5"
Projection Distance	2.62' - 16.4' (0.8 - 5m)	3.2' - 16.4' (1.0 - 5m)	3.2' - 29.5' (1 - 9m)	4.43' - 26.5' (1.35 - 8.08m)	4.92' - 32.8' (1.5 - 10m)	6.56' - 65.6' (2 - 20m)	9.84' - 65.6' (3 - 20m)
Lens Shift Range	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%	Ver.: -15% to +55% Hor.: -5% to +5%

TEL: +1-855-885-2378 | WWW.VIVITEKUSA.COM | 46101 FREMONT BLVD., FREMONT, CA 94538 USA

*Note: Using Regular Lens

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.